BC-0905A

Camelion

Battery Charger

AA/AAA



Camelion.











Camelion.



BC-0905A

Charges:

1-4 × 🔼

1-4 × 🗚




Ni-MH

Ni-Cd











Main Features

- 4 Independent Charging Channels
- 6 Level Charge Protections

-△V Cut Off

Timer Control Protection

Over Temperature Protection

Reverse Polarity Protection

Over current and Short Circuit Protection

Defective and Non-rechargeable Battery Detection

- Trickle Charge
- Switch and Match Plugs
- LED Indicators

| Red | Charging |
|----------|---|
| Flashing | Defective or non-rechargeable batteries / |
| | Short circuit |
| Green | Fully charged / Trickle |

Specifications

Input: 100-240V~50/60Hz

Output: AA: 1A (1-2 pcs),

0.5A (3-4 pcs)

AAA: 0.6A (1-2 pcs),

0.3mA (3-4 pcs)

Charging Time*

| Battery Type | Charging Time(Appr.) | |
|------------------|----------------------|-----------|
| | 1-2 Cells | 3-4 Cells |
| Ni-MH AA 2700mAh | 3 hrs | 6 hrs |
| Ni-MH AA 2000mAh | 2.5 hrs | 4.5 hrs |
| Ni-MH AA 1500mAh | 2 hrs | 3.5 hrs |
| Ni-MH AAA 800mAh | 100 min | 3 hrs |
| Ni-Cd AA 1000mAh | 70 min | 2 hrs |
| Ni-Cd AAA 300mAh | 40 min | 70 min |

^{*} The charging time varies according to different batteries. For a more complete listing please visit http://www.camelionbatterv.com/en/about.aspx?Tvpeld=10932